

Cast Stone Wasbasins (cultured marble)



Main Characteristics of Material



Cast stone material consists of 80% MARBLEMIX natural filler – calcium carbonate and quartz particles, and 20% AOC binder – polyester resins.

- Stable, firm, durable material; smooth and glossy surface
- Non-porous, not absorbing moisture, dirt repelling
- Good resistance to UV-irradiation, high t^0 , fire, stains
- Inert to all kind of chemicals
- Easy to maintain and clean
- Good repair / renovation possibilities, easy to polish and make small repair works at site
- Wide colour range as well as NCS and RAL colour codes
- White colour standard used - Alpine White, Sanitec standard



Scratch Resistant Surface



0.8 – 1.0 mm Gelcoat layer produced by ASHLAND provides scratch resistant surface.
All ASHLAND products are certified and have passed European product quality requirements.
AmfiTop works with the newest ASHLAND products that are available without exclusivity restrictions.



New Project Policy



- AmfiTop manufactures the new product exclusively for the customer
- AmfiTop provides a mutual cooperation in designing new products
- The customer covers prototyping and tooling costs
- The customer holds ownership for the new design pattern, prototypes, casting moulds and tooling



Cooperation Values



- AmfiTop has many years of experience in cooperative project development
- We have built good relations with all our partners providing reliable product supply
- AmfiTop will provide the best design and manufacturing solutions for small and mid range product series
- AmfiTop organises productions based on made-to-order principles thus providing high flexibility within reasonable lead times

